

Haier

Under-counter Models **Offering Accessibility**



HYC-118A
HYC-118



HYC-118A



HYC-118

Under-counter Pharmacy Refrigerator



Reliability

- Electrically heated glass door to prevent condensation (for model HYC-118A)
- High efficiency specialty compressor with known field reliability
- Permanently lubricated cooling fan for safety and longevity
- Forced-air cooling with optimized air distribution system designed to achieve maximum temperature uniformity and stability
- Optimized refrigeration system design for more effective cooling and speedy recovery

Key Features

- Adjustable temperature range 2~8°C
- Microprocessor control, LED digital display and temperature adjustment with an increment of 1°C
- Designed for ambient temperature 10~32°C with humidity below 60%

Safety

- Equipped with a complete temperature alarm system featuring audible buzzer and visual flashing light
- Capable of alerting failures due to high and low temperature, sensor error, door ajar
- Safety lock to prevent unauthorized access

Technical Data		HYC-118A	HYC-118
Electrical Data	Climate Class	N	N
	Power Supply(V/Hz)	220-240/50	220-240/50
	Power(W)	160	160
	Electrical Current(A)	1.05	1.05
Dimensions	Capacity(L/Cu.Ft)	118/4.2	118/4.2
	Net/Gross Weight(approx)	46/51(kg)	41/46(kg)
		101.4/112.4(lbs)	90.4/101.4(lbs)
	Interior Dimensions(W*D*H)	512*415*638(mm)	512*415*638(mm)
		20.2*16.3*25.1(in)	20.2*16.3*25.1(in)
	Exterior Dimensions(W*D*H)	597*645*835(mm)	597*645*835(mm)
Accessories		23.5*25.4*32.9(in)	23.5*25.4*32.9(in)
	Packing Dimensions(W*D*H)	675*680*930(mm)	675*680*930(mm)
		26.6*26.8*36.6(in)	26.6*26.8*36.6(in)
	Container load (20'/40'/40'H)	48/102/102	48/102/102
	Test Hole	Y	Y
	Shelves/Inner doors	3/-	3/-